



		902	904	904 X	907
Device	High-resolution, daylight-readable color TFT display				•
	High-contrast static segment display	•	•	•	
	Open, easy-to-clean quiver	•	•	•	•
	Carrying strap	•	•	•	•
	Real-time clock	•	•	•	•
	Replaceable Li-ion battery, USB-chargeable in the device		•		•
	MemoLog – Logger for Memosens calibration data		•	•	•
	Multiple languages				•
	Multiparameter version for pH, ORP, conductivity and oxygen			•	•
Sensors	SE 340 optical oxygen sensor				•
	Analog pH sensors with DIN plug	•	•	•	•
	Analog conductivity sensors	•	•	•	•
	Memosens sensors	•	•	•	•
Connections/Software	USB port for software update and communication		•	•	•
	Paraly SW 112 PC software for communication with PC		•	•	•
Calibration	Calibration with Calimatic automatic buffer recognition	•	•	•	•
	Calibration by data entry	•	•	•	•
	Manual calibration by entering individual buffer values	•	•	•	•
	Calibration timer (can be switched off)	•	•	•	•
Data storage	Data logger for automatic recording of measured values		•	•	•
	Data memory (number of storable values)		5,000	5,000	10,000
ATEX approval	Zone 0/1			•	